

So sollen Fensterläden sein. Perfektion und Beständigkeit aus Aluminium.
 Le volet aluminium tel que vous l'imaginez. Perfection et pérennité.
 Exactly the way window shutters should be. Perfection and stability made from aluminium.



MODEL Z

ALUMINIUM WINDOW SHUTTER WITH ALUMINIUM LAMELLAE



TECHNICAL DESCRIPTION

FABRICATION	The frame profiles are cut straightly and using transom profile on top and on bottom screwed doubly. Manual reworking of mitre edges, assembly of lamellae and subsequent coating of entire shutter, including lamellae.
SURFACE FINISH	Powder-coating at 200° C to customer requirements and in accordance with Qualicoat guidelines (lic. no. 3300). Standard colours as per RAL, NCS, NCS-S, VSR. Standard surface finishes: satin, matt and finely structured matt. Colours and finishes can also be supplied to customers' specific requirements.
PROFILES AND CORNER JOINTS	<p>Frame profile : Extruded aluminium profile 70 x 6 mm – lateral Extruded aluminium profile 71 x 33 mm – on top and on bottom</p> <p>Lamellae profile: Extruded aluminium profile in "Z" form 54 x 58 mm</p> <p>Corner joints: Double vissage of the lateral profiles</p>
LAMELLAE DISTANCE	on customer request
OPTIONS	<input type="checkbox"/> Miscellaneous arched designs and chamfered edges <input type="checkbox"/> Notches <input type="checkbox"/> Swing-out shutter panel <input checked="" type="checkbox"/> Two-tone <input type="checkbox"/> Lock installation <input type="checkbox"/> Rebate strip
SHUTTER SIZES	Shutter width: from min. 325 mm to max. 1600 mm Shutter height: from min. 390 mm to max. 3500 mm
WEIGHT	15,0 kg/m ² approx.



MODEL Z

ALUMINIUM WINDOW SHUTTER WITH ALUMINIUM LAMELLAE

WEITERE INFORMATIONEN:

<p>VARIANTS AND INSTALLATION POSSIBILITIES</p>	<p>Rabbit strips:</p> <p><input type="checkbox"/> Rabbit T-strip <input type="checkbox"/> Rabbit strip with rubber seal <input type="checkbox"/> Rabbit strip with brush seal</p> <p>Transoms & mullions:</p> <p><input checked="" type="checkbox"/> Transoms <input type="checkbox"/> Screwed lamellae available <input type="checkbox"/> Mullions <input type="checkbox"/> Transom and mullion</p> <p>Configuration:</p> <p><input type="checkbox"/> Hinged Shutter (masonry and window frame installation) <input checked="" type="checkbox"/> Sliding shutter <input type="checkbox"/> Sliding bi-fold shutter <input type="checkbox"/> Dummy shutters</p> <p>Drives:</p> <p><input type="checkbox"/> Crank for hinged shutters <input type="checkbox"/> Electric drive for hinged shutters <input checked="" type="checkbox"/> Electric drive for sliding shutters</p>
<p>ASSEMBLY SYSTEMS AND PRE-ASSEMBLY</p>	<p>Assembly systems:</p> <p><input type="checkbox"/> SystemFix <input type="checkbox"/> JustierFix <input type="checkbox"/> Assembly frame (complete pre-assembly in the factory)</p> <p>Optional pre-assembly in the factory:</p> <p><input type="checkbox"/> JustierFix <input checked="" type="checkbox"/> Sliding shutter preparation <input type="checkbox"/> Sliding bi-fold shutter preparation</p>

GENERAL INFORMATION:

<p>FUNCTION AND SUITABILITY</p>	<p>Functional shading element for providing protection from heat and light irradiation, and as a stylistic element in facade design. Non-fading, colour-fast and water-repellent surface finish.</p>
<p>DELIVERY TIME</p>	<p>4-5 weeks after finalization of order or by arrangement.</p>
<p>DISPATCH</p>	<p>Delivery with our own vehicles, by haulier or collection by the customer also possible.</p>
<p>SALES AND DELIVERY TERMS</p>	<p>See General Terms & Conditions of sale in the current price list or at www.ast.eu respectively.</p>

