

So sollen Fensterläden sein. Perfektion und Beständigkeit aus Aluminium.
 Voici des volets aluminium. La perfection et pérennité.
 Exactly the way window shutters should be. Perfection and stability made from aluminium.

A.S.T



MODEL C-H

ALUMINIUM WINDOW SHUTTER WITH CAVITY FILLING

TECHNICAL DESCRIPTION

FABRICATION	The frame profiles are mitred and joined at right angles using special press-fit internal connectors. Manual reworking of mitre edges and subsequent coating of entire shutter, including lamellae.
SURFACE FINISH	Powder-coating at 200° C to customer requirements and in accordance with Qualicoat guidelines (lic. no. 3300). Standard colours as per RAL, NCS, NCS-S, VSR. Standard surface finishes: satin, matt and finely structured matt. Colours and finishes can also be supplied to customers' specific requirements.
PROFILES AND CORNER JOINTS	<p>Frame profile : Extruded aluminium profile 71 x 33 mm</p> <p>Lamellae profile or panel: Extruded aluminium profile 100 x 18 mm</p> <p>Transom profile: Extruded aluminium profile 71 x 33 mm</p> <p>Corner joints: Special die cast corner connectors</p>
TYPES	<p>C-HH The grooves run in a horizontal direction</p> <p>C-HV The grooves run in a vertical direction</p> <p>C-HS The grooves run in a 45 ° diagonal direction</p>
OPTIONS	<p><input checked="" type="checkbox"/> Miscellaneous arched designs and chamfered edges</p> <p><input checked="" type="checkbox"/> Notches</p> <p><input type="checkbox"/> Swing-out shutter panel</p> <p><input checked="" type="checkbox"/> Two-tone</p> <p><input checked="" type="checkbox"/> Lock installation</p> <p><input checked="" type="checkbox"/> Rebate strip</p>
SHUTTER SIZES	<p>Shutter width: from min. 250 mm to max. 1600 mm</p> <p>Shutter height: from min. 250 mm to max. 3500 mm</p>
WEIGHT	11,0 kg/m2 approx.



MODEL C-H

ALUMINIUM WINDOW SHUTTER WITH CAVITY FILLING

WEITERE INFORMATIONEN:

VARIANTS AND INSTALLATION POSSIBILITIES	<p>Rabbit strips:</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Rabbit T-strip <input checked="" type="checkbox"/> Rabbit strip with rubber seal <input checked="" type="checkbox"/> Rabbit strip with brush seal <p>Transoms & mullions:</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Transoms <input type="checkbox"/> Screwed lamellae available <input checked="" type="checkbox"/> Mullions <input checked="" type="checkbox"/> Transom and mullion <p>Configuration:</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Hinged Shutter (masonry and window frame installation) <input checked="" type="checkbox"/> Sliding shutter <input type="checkbox"/> Sliding bi-fold shutter <input checked="" type="checkbox"/> Dummy shutters <p>Drives:</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Crank for hinged shutters <input checked="" type="checkbox"/> Electric drive for hinged shutters <input checked="" type="checkbox"/> Electric drive for sliding shutters
ASSEMBLY SYSTEMS AND PRE-ASSEMBLY	<p>Assembly systems:</p> <ul style="list-style-type: none"> <input type="checkbox"/> SystemFix <input type="checkbox"/> JustierFix <input type="checkbox"/> Assembly frame (complete pre-assembly in the factory) <p>Optional pre-assembly in the factory:</p> <ul style="list-style-type: none"> <input type="checkbox"/> JustierFix <input checked="" type="checkbox"/> Sliding shutter preparation <input checked="" type="checkbox"/> Sliding bi-fold shutter preparation

GENERAL INFORMATION:

FUNCTION AND SUITABILITY	Functional shading element for providing protection from heat and light irradiation, and as a stylistic element in facade design. Non-fading, colour-fast and water-repellent surface finish.
DELIVERY TIME	4 weeks after finalization of order or by arrangement.
DISPATCH	Delivery with our own vehicles, by haulier or collection by the customer also possible.
SALES AND DELIVERY TERMS	See General Terms & Conditions of sale in the current price list or at www.ast.eu respectively.

