

So sollen Fensterläden sein. Perfektion und Beständigkeit aus Aluminium.
 Voici des volets aluminium. La perfection et pérennité.
 Exactly the way window shutters should be. Perfection and stability made from aluminium.

A.S.T



MODEL H ALU60

THE SLIDING SHUTTER WITH TRAPEZOIDAL LAMELLAE

TECHNICAL DESCRIPTION

FABRICATION	The frame profiles are mitred and joined at right angles using special press-fit internal connectors. Manual reworking of mitre edges and subsequent coating of entire shutter, including lamellae.
SURFACE FINISH	Powder-coating at 200° C to customer requirements and in accordance with Qualicoat guidelines (lic. no. 3300). Standard colours as per RAL, NCS, NCS-S, VSR. Standard surface finishes: satin, matt and finely structured matt. Colours and finishes can also be supplied to customers' specific requirements.
PROFILES AND CORNER JOINTS	<p>Frame profile : Extruded aluminium profile 40 x 32 mm (L-profile)</p> <p>Lamellae profile: Extruded aluminium profile 60 x 15 mm</p> <p>Corner joints: Special corner connectors of extruded aluminium profile</p>
LAMELLAE DISTANCE	Standard distance between lamellae: 7 respectively 12 mm
OPTIONS	<input type="checkbox"/> Miscellaneous arched designs and chamfered edges <input type="checkbox"/> Notches <input type="checkbox"/> Swing-out shutter panel <input checked="" type="checkbox"/> Two-tone <input type="checkbox"/> Lock installation <input type="checkbox"/> Rebate strip
SHUTTER SIZES	Shutter width: from min. 325 mm to max. 1800 mm Shutter height: from min. 390 mm to max. 3000 mm
WEIGHT	10.0 kg/m ² approx.



MODEL H ALU60

THE SLIDING SHUTTER WITH TRAPEZOIDAL LAMELLAE

WEITERE INFORMATIONEN:

<p>VARIANTS AND INSTALLATION POSSIBILITIES</p>	<p>Rabbet strips:</p> <ul style="list-style-type: none"> <input type="checkbox"/> Rabbet T-strip <input type="checkbox"/> Rabbet strip with rubber seal <input type="checkbox"/> Rabbet strip with brush seal <p>Transoms & mullions:</p> <ul style="list-style-type: none"> <input type="checkbox"/> Transoms <input type="checkbox"/> Screwed lamellae available <input checked="" type="checkbox"/> Mullions <input type="checkbox"/> Transom and mullion <p>Configuration:</p> <ul style="list-style-type: none"> <input type="checkbox"/> Hinged Shutter (masonry and window frame installation) <input checked="" type="checkbox"/> Sliding shutter <input checked="" type="checkbox"/> Sliding bi-fold shutter <input checked="" type="checkbox"/> Dummy shutters <p>Drives:</p> <ul style="list-style-type: none"> <input type="checkbox"/> Crank for hinged shutters <input type="checkbox"/> Electric drive for hinged shutters <input checked="" type="checkbox"/> Electric drive for sliding shutters
<p>ASSEMBLY SYSTEMS AND PRE-ASSEMBLY</p>	<p>Assembly systems:</p> <ul style="list-style-type: none"> <input type="checkbox"/> SystemFix <input type="checkbox"/> JustierFix <input type="checkbox"/> Assembly frame (complete pre-assembly in the factory) <p>Optional pre-assembly in the factory:</p> <ul style="list-style-type: none"> <input type="checkbox"/> JustierFix <input checked="" type="checkbox"/> Sliding shutter preparation <input checked="" type="checkbox"/> Sliding bi-fold shutter preparation

GENERAL INFORMATION:

<p>FUNCTION AND SUITABILITY</p>	<p>Functional shading element for providing protection from heat and light irradiation, and as a stylistic element in facade design. Non-fading, colour-fast and water-repellent surface finish.</p>
<p>DELIVERY TIME</p>	<p>4 weeks after finalization of order or by arrangement.</p>
<p>DISPATCH</p>	<p>Delivery with our own vehicles, by haulier or collection by the customer also possible.</p>
<p>SALES AND DELIVERY TERMS</p>	<p>See General Terms & Conditions of sale in the current price list or at www.ast.eu respectively.</p>

